



FEATURES

- Super bright 1800 lumen 6500k spot beam LED
- With additional 1000 lumen 6500k COB LED floodlight
- Super tough polycarbonate, ABS and aluminium construction
- Glow-in-the-Dark strip around reflector for extra visibility
- Easy press dual switches for easy mode selection
- Convenient shoulder carry strap included
- Threaded hole in the base for attaching to a tripod
- IPX6 Water proof
- Super high power 3.7v 18,000mAh li-ion battery
- Battery level and charging indicators
- Multiple USB power bank outputs - 5V 3A / 9V 2A / 12V 1A
- Intelligent multiple USB-C charging inputs - 5V 3A / 9V 2A
- Faster 2A and 3A charging - 7 or 8 hours charge time
- 1m USB-C charging cable included

BATTERY - 3.7v 18,000mAh Li-ion Rechargeable Battery

WEIGHT - 773g

DIMENSIONS - 108 x 200 x 131mm

ADVICE & IMPORTANT INFORMATION!

LEDs will become hot when switched on; do not touch and never place face down on any surface – risk of fire! Even once the lamp has been switched off, DO NOT place face down as the LEDs will stay hot/warm for a while.

Do not look directly at the LED. Do not operate in direct sunlight or extreme temperature conditions (below -20°C or above 60°C).

Do not use the device if there is any visible damage to the housing, charge port, lenses, switches or cable. Take care when using a USB plug adaptor, check for any damage. DO NOT exceed the stated charging inputs or damage may occur to the internal battery and may void the warranty.

The rechargeable battery will reach full performance after a few complete charging and discharging cycles.

To keep the rechargeable battery in optimum condition, it should be recharged every 3-6 months, especially if it is not being used for a long period of time. Always fully charge batteries before storage.

Always protect lithium batteries from heat, intense sunlight, fire, water and moisture – danger of explosion!

If a battery is damaged, fluids can leak out. AVOID contact as this can lead to skin irritation and/or burns. If skin contact occurs, rinse thoroughly with water. If irritation persists, seek medical advice. Seek immediate medical assistance if lithium battery fluid comes into contact with the eyes.

Children under 12 years of age should only use the product under adult supervision.

Do not open, disassemble or attempt to modify the product; this will void the warranty and can be dangerous. Improper use or modification is not covered under the warranty.

Take care not to let the lenses come into contact with hard/sharp objects, damage/scratches to the lenses will affect light output.

This product is water resistant to IPX6. If the product has been subjected to excessive water the warranty may be void.

This product has a 1 year standard warranty (or extended to 2 years once registered online at WWW.UNILITE.CO.UK) against manufacturing faults and defects. It does not cover normal wear and tear, modifications, accidental damage or poor maintenance. Unilite warranties do not cover battery leaks or the use of incorrect chargers and cables that can damage batteries. Do not dispose of this device in normal household waste. It must be disposed of via an authorised electrical appliance disposal centre or at your local waste disposal unit. Please re-use or recycle packaging where possible.

Keep these instructions for future reference or for subsequent possessors.

ANSI FL 1 Standard



Beam Type	Lumens	Beam Distance (M)	Runtime (H)
SPOT BEAM - HIGH	1800	760 M	9 H
SPOT BEAM - MID	1000	525 M	14 H
SPOT BEAM - LOW	400	345 M	37 H
FLOOD LIGHT - LOW	375	22 M	25 H
FLOOD LIGHT - HIGH	1000	34 M	9 H
RED FLOOD - STATIC	25	--	78 H
RED FLOOD - FLASH	25	--	390 H

OPERATION

TOP SWITCH: White Spot Beam Mode

Switch Sequence: HIGH > MEDIUM > LOW > OFF.

[If left in any setting for over 3 seconds, the next press will turn the lamp off]

BOTTOM SWITCH: Floodlight & Red Mode

Switch Sequence: WHITE LOW > WHITE HIGH > RED STATIC > RED FLASH > OFF.

[If left in any setting for over 3 seconds, the next press will turn the lamp off]



CHARGING

1. Only use a USB-C charging cable.
2. Lift the charging port cover on the end of the lamp.
3. Plug the USB-C end of the cable into the USB-C charge port.
4. Plug the USB end of the cable into a USB charging port (only use a charger with 5V 3A or 9V 2A output or damage may occur to the internal battery).
5. Charge Time: 5V 3A = 8 hours or 9V 2A = 7 hours

(PRODUCT CAN BE USED WHILE RECHARGING)

The lamp can also be used as a Power Bank, with 5V 3A, 9V 2A, 12V 1A outputs. Plug the USB end of your device charging cable into the USB port.

Warranty void if not used with the stated charger specifications



- Power indicator**
- 75%–100%
 - 50%–75%
 - 25%–50%
 - 5%–25%
 - <5%
- Recharging indicator**
- <25%
 - 25%–50%
 - 50%–75%
 - 75%–100%
 - 100%

Charging & Power Indicators

Charging Port & Power Bank



